

## Claims

1. Inhalation device for creating an aerosol, comprising:
  - aerosol means, for creating an aerosol in the device,
  - 5 - control means, for adjusting the state and condition of the aerosol, in order to manipulate the characteristics of the aerosol, such as uniformity and mean particle size, and
  - an opening, for releasing the aerosol from the device,wherein:
  - the device is provided with supply means, for adding a substance to the aerosol, prior to or
  - 10 upon release of the aerosol from the opening, in order to release the substance from the opening using the aerosol as a carrier.
2. Device according to claim 1, wherein the aerosol means comprises a mist generator.
- 15 3. Device according to claim 1, wherein the aerosol means comprises a catalytic burner, such as a fuel cell.
4. Device according to one of the preceding claims, wherein the device comprises an aerosol chamber for creating the aerosol in said chamber.
- 20 5. Device according to one of the preceding claims, wherein the control means are adapted to add energy to or remove energy from the aerosol in order to thereby control the particle size of the aerosol.
- 25 6. Device according to one of the preceding claims, wherein the control means comprises a condensation chamber.
7. Device according to claim 6, wherein the condensation chamber has a first open end to receive a flow and a second open end to release a flow.
- 30 8. Device according to claim 4 and either claim 6 or 7, wherein the condensation chamber adjoins the aerosol chamber.

9. Device according to one of the preceding claims, wherein the control means comprises a heat exchanger provided with apertures for allowing the aerosol to pass through the heat exchanger.

5 10. Device according to one of the claims 6 to 9, wherein the device comprises a Peltier-element, positioned in the condensation chamber, to retrieve condensation energy.

11. Device according to one of the preceding claims, wherein the control means comprises dilution means for mixing the aerosol with a fluid, such as an unsaturated gas, for thereby  
10 decreasing the dew point of the aerosol.

12. Device according to one of the preceding claims, wherein the supply means comprises means for adding a gaseous substance to the aerosol.

15 13. Device according to claim 12, wherein the supply means comprises a container, such as a canister, for storing a gaseous substance.

14. Device according to one of the preceding claims, wherein the supply means comprises means for adding a liquid substance to the aerosol.

20

15. Device according to claim 14, wherein the supply means comprises a membrane pump.

16. Device according to one of the preceding claims, wherein the supply means comprises means for adding a solid substance to the aerosol.

25

17. Device according to claim 14 or 16, wherein the supply means comprises a container for storing a propellant, such as CO<sub>2</sub>, and a liquid and/or solid substance.

18. Device according to one of the preceding claims, wherein the device is adapted to be  
30 breath actuated.

19. Device according to one of the preceding claims, wherein the device is provided with means for operating the device with a breath support.

20. Device according to one of the preceding claims, wherein the control means are coupled with process means, provided with storage means, for receiving and processing data relating to a preferred state and condition of the aerosol to be released.
- 5 21. Device according to claim 20 wherein the device is provided with sensor means, coupled with the process means, to measure data relating to the state and condition of the aerosol to be released.
22. Device according to one of the preceding claims, wherein the supply means are coupled  
10 with process means, provided with storage means, for receiving and processing data relating to a preferred timing of the adding of the substance to the aerosol.
23. Device according to claim 22 wherein the device is provided with sensor means, coupled with the process means, to measure data relating to the timing of the adding of the substance  
15 to the aerosol.
24. Device according to claim 21 or 23, wherein the sensor means comprise flow measurement means for producing a measure of volume released.
- 20 25. Method for creating an aerosol in an inhalation device, comprising the steps of:  
a) creating an aerosol by means of aerosol means in the inhalation device,  
b) adjusting the state and condition of the aerosol, in order to manipulate the characteristics of the aerosol, such as uniformity and mean particle size, and  
c) releasing the aerosol from an opening of the device,  
25 wherein the method comprises the step of:  
d) adding a substance to the aerosol, prior to upon release of the aerosol from the device in order to release the substance from the opening using the aerosol as a carrier.
26. Method according to claim 25, wherein the method comprises the steps of:  
30 e) prior to step b) identifying a preferred state and condition of the aerosol to be released from the device.
27. Method according to claim 25 or 26, wherein step d) is executed after the completion of step b).

28. Method according to one of claims 25 to 27, wherein step b) is repeated after the completion of step d).

5 29. Method according to one of claims 25 to 28, wherein the method comprises the step of:  
f) measuring the actual flow through the device, and  
g) using this measurement in order to control the manipulation of the aerosol in step b).

30. Method according to one of claims 25 to 29, wherein the method comprises the step of:  
10 h) prior to step b) evaluating the heat content of the aerosol in order to thereby determine the specific amount of energy to be added or extracted from the aerosol in order to realise the desired manipulation of the aerosol.

31. Method according to one of claims 25 to 30, wherein the manipulation of the aerosol  
15 comprises a condensation step, for allowing condensation of at least part of the gaseous phase of the aerosol.

32. Method according to claim 31, wherein the manipulation of the aerosol is adapted to obtain an aerosol with a relative humidity of 100%.

20

33. Method according to one of claims 25 to 32, wherein the manipulation of the aerosol comprises a dilution step, for mixing the aerosol with a fluid, such as an unsaturated gas, for thereby decreasing the dew point of the aerosol.

25 34. Method according to one of claims 26 to 33, wherein the method comprises the step of:  
i) using the results of steps e) and f) to calculate a preferred timing for the adding of the substance to the aerosol.

35. Method according to one of claims 25 to 34, wherein the method comprises the step of  
30 creating in step a) an aerosol containing a first substance and adding in step d) a further substance to said aerosol.